

## Product Datasheet uvex 1 G2 68371 - 68374 S1 P SRC

**UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth**

<b>General features</b>	<ul style="list-style-type: none"><li>• ultra-lightweight perforated S1 P safety shoe</li><li>• made from synthetic materials, making it suitable for people allergic to chrome</li><li>• all sole materials are free of silicone, plasticisers and other paint wetting impairment substances</li><li>• individually adjustable elastic laces for quick release, normal laces also provided</li></ul>
<b>Protection features</b>	<ul style="list-style-type: none"><li>• new, innovative uvex i-PUREnrj sole technology with the highest level of shock-absorbing properties at the forefoot and at the heel, excellent rebound over the entire midsole and optimal stability thanks to the foam heel basket</li><li>• meets the ESD specification with volume resistance under 35 megaohms</li><li>• new wider 100% metal-free uvex xenova® safety toe cap for more toe room and optimum fit – compact design, anatomical shape, good lateral stability and no thermal conductivity</li><li>• penetration-resistant, non-metallic midsole in accordance with current safety standards, does not restrict flexibility of the shoe</li><li>• TPU scuffcap to protect against abrasion</li></ul>
<b>Comfort features</b>	<ul style="list-style-type: none"><li>• outstanding wearer comfort thanks to a newly developed last and climate-optimised, breathable materials</li><li>• virtually seam-free, perforated upper in high-tech microvelour to eliminate pressure points</li><li>• removable antistatic comfortable insole with a</li></ul>

	<p>moisture transport system, additional shock absorption around the heel and forefoot and excellent support for the arch</p> <ul style="list-style-type: none"> <li>• soft padding on the dust tongue and collar</li> <li>• sizes 35 to 40 have been produced using a women's last</li> </ul>																				
<b>Outsole</b>	<ul style="list-style-type: none"> <li>• ergonomically designed uvex x-tended grip outsole incorporates the latest biomechanical research, is particularly durable and therefore offers excellent slip resistance. The tread is particularly suited to industrial floors and rough surfaces</li> <li>• excellent cushioning and extremely flexible</li> <li>• excellent slip resistance, self-cleaning tread</li> <li>• resistant to oil and petrol</li> <li>• resistant to temperatures for short periods up to +120°C</li> </ul>																				
<b>Certificates</b>	<ul style="list-style-type: none"> <li>• Certified with uvex medicare for individual, orthopedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.</li> </ul>																				
<b>Areas of application</b>	<ul style="list-style-type: none"> <li>• light applications</li> </ul>																				
<b>Technical data</b>	<p>uvex 1 G2 perforated safety shoe S1 P SRC</p> <table> <tr> <td>Art.-no.</td> <td>68371</td> <td>68372</td> <td>68373</td> <td>68374</td> </tr> <tr> <td>Width</td> <td>10</td> <td>11</td> <td>12</td> <td>14</td> </tr> <tr> <td>Standard</td> <td colspan="4">EN ISO 20345:2011 S1 P SRC</td> </tr> <tr> <td>Size</td> <td colspan="4">35-52</td> </tr> </table>	Art.-no.	68371	68372	68373	68374	Width	10	11	12	14	Standard	EN ISO 20345:2011 S1 P SRC				Size	35-52			
Art.-no.	68371	68372	68373	68374																	
Width	10	11	12	14																	
Standard	EN ISO 20345:2011 S1 P SRC																				
Size	35-52																				
<b>Accessories</b>	<p><i>Removable uvex 1 G2 comfortable climatic insole</i> (article no.: 94907 - 94900)</p> <ul style="list-style-type: none"> <li>• improved full-surface shock absorption</li> <li>• ultra-breathable, moisture-absorbing and quick-drying materials</li> <li>• shock absorption zones support natural movement of the foot</li> <li>• non-irritating, comfortable surface structure</li> <li>• anti-static properties</li> <li>• arch support</li> </ul> <p><i>Laces</i></p> <ul style="list-style-type: none"> <li>• black (Art.-no.: 9599.9 09)</li> <li>• elastic laces (Art.-no.: 9591.200)</li> </ul>																				